

**MACHINE SPECIFICATIONS**

\*Specifications subject to change without notice.

<b>MODEL</b>	<b>SW-50R</b>	<b>SW-50HT</b>	<b>SW-50EX</b>
<b>WORK CAPACITY</b>			
HEIGHT	50"	50"	50"
TURNTABLE DIA.	28"	28"	28"
LOAD WEIGHT	1,500 LBS	1,500 LBS	1,500 LBS
<b>FLOOR SPACE REQUIRED</b>			
HEIGHT	93"	93"	93"
WIDTH	57"	57"	73"
LENGTH: DOOR OPEN	98"	98"	98"
DOOR CLOSED	57"	68"	68"
TURNTABLE HEIGHT (ABOVE FLOOR)	32"	32"	32"
SHIPPING WEIGHT	2,100 LBS	2,400 LBS	2,800 LBS
<b>CLEANING SYSTEM</b>			
SOLUTION CAPACITY	110 gals.	140 gals.	160 gals
PUMP MOTOR	10 HP	10 HP	10 HP
PUMP OUTPUT	80 psi @ 140 gpm	80 psi @ 140 gpm	80 psi @ 140 gpm
SPRAY NOZZLES	24 alternating	24 alternating	24 alternating
FILTER SCREEN	1200 sq."	1450 sq."	2530 sq."
<b>CABINET CONSTRUCTION</b>			
GAUGE STEEL	12 gauge	12 gauge	12 gauge
INSULATION	1" fiberglass	1" fiberglass	1" fiberglass
STEAM VENT	6"	6"	6"
GAS VENT	6"	6"	6"
<b>HEAT SOURCE</b>			
ELECTRIC ELEMENT	12 kW	12 kW	15 kW
GAS BURNER	100,000 BTU	100,000 BTU	150,000 BTU
<b>HOT TANK BASKETS</b>			
WIDTH (I.D.)	13"	24"	24"
LENGTH (I.D.)	34"	34"	55"
DEPTH (I.D.)	11"	11"	11"
<b>ELECTRICAL REQ.</b>			
PUMP MOTOR 3 PHASE	208/230/*460 Volts 25-24-12 Amps		
ELECTRICAL HEAT 3 PHASE	(12 KW) 208/230/460 Volts 33-29-17 Amps	(12 KW) 208/230/460 Volts 33-29-17 Amps	(15 KW) 208/230/460 Volts 41-37-19 Amps
ELECTRIC HEATER 1 PHASE	(12 KW) 230 Volts 52 Amps	(12 KW) 230 Volts 52 Amps	(15 KW) 230 Volts 65 Amps
<b>STANDARD EQUIPMENT</b>			
LOW WATER SWITCH	STANDARD		
DUAL 7 DAY TIMERS	STANDARD		
DIGITAL TEMP CONTROLLER	STANDARD		
HEAD RACK/CRANK RACK	STANDARD		
AUTO AIR INDUCER	STANDARD		
SHORT CIRCUIT PROTECTION	STANDARD		
THERMAL PROTECTION	STANDARD		
LAY DOWN DOOR/SEALESS	STANDARD		
V-BOTTOM FLOOR	STANDARD		
BUILT IN HOT TANK	STANDARD		
360 DEGREE MANIFOLD	STANDARD		
PNEUMATIC DOOR CLAMP	STANDARD		
WARRANTY	ONE YEAR		