

**MACHINE SPECIFICATIONS**

\*Specifications subject to change without notice.

<b>MACHINE SPECIFICATIONS</b>		
<b>*Specifications subject to change without notice.</b>		
	<b>SW-3660 ELECTRIC HEAT</b>	<b>SW-3660 GAS HEAT</b>
<b>WORK CAPACITY</b>		
HEIGHT	60"	60"
TURNTABLE DIA.	36"	36"
LOAD WEIGHT	2000 LBS	2000 LBS
<b>FLOOR SPACE REQUIRED</b>		
HEIGHT	110"	110"
WIDTH	69"	69"
WIDTH w/ OIL SKIMMER	81"	81"
LENGTH: DOOR OPEN	118"	118"
DOOR CLOSED	77"	77"
LOADING HEIGHT ABOVE FLOOR	32"	32"
SHIPPING WEIGHT	3000 LBS	3000 LBS
<b>CLEANING SYSTEM</b>		
SOLUTION CAPACITY	225 gals.	225 gals.
PUMP MOTOR	15 HP	15 HP
PUMP OUTPUT	80 psi @ 225 gpm	80 psi @ 225 gpm
SPRAY NOZZLES	27 alternating	27 alternating
FILTER SCREEN	2550 sq."	2550 sq."
<b>CABINET CONSTRUCTION</b>		
GAUGE STEEL	12 gauge	12 gauge
INSULATION	1" fiberglass	1" fiberglass
STEAM VENT	6"	6"
GAS VENT	6"	6"
<b>HEAT SOURCE</b>		
ELECTRIC ELEMENT	21.5W	N/A
GAS BURNER	N/A	180,000 BTU
<b>HOT TANK BASKET</b>		
WIDTH (I.D.)	24	24"
LENGTH (I.D.)	44"	44"
DEPTH (I.D.)	11"	11"
<b>ELECTRICAL REQ.</b>		
PUMP MOTOR 3 PHASE AMP DRAW	208/230/*460 Volts 38-34-17 Amps	
ELECTRICAL HEAT 3 PHASE AMP DRAW	208/230/460 Volts 60-52-26 Amps	N/A
<b>STANDARD EQUIPMENT</b>		
LOW WATER CUT OFF SWITCH	ELECTRIC HEAT ONLY	
DUAL 7 DAY TIMERS	STANDARD	
DIGITAL TEMP CONTROLLER	STANDARD	
HEAD RACK/CRANK RACK	STANDARD	
AUTO AIR INDUCER	STANDARD	
SHORT CIRCUIT/THERMAL PROTECTION	STANDARD	
LAY DOWN DOOR/SEALESS	STANDARD	
V-BOTTOM FLOOR	STANDARD	
BUILT IN HOT TANK	STANDARD	
MOISTURE PROOF ELECTRONICS	STANDARD/GAS MACHINES	
360 DEGREE MANIFOLD	STANDARD	
PNEUMATIC DOOR CLAMP	STANDARD	
WARRANTY	ONE YEAR	