

TUMBLE CLEANING MACHINE SPECIFICATIONS

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

SPECIFICATIONS	TB-10	TB-20	TB-30
GEAR MOTOR	¼ HP @ 40 rpm	½ HP @ 40 rpm	½ HP @ 40 rpm
MOTOR TORQUE RATING	300 (In. Lbs)	700 (In. Lbs)	700 (In. Lbs)
COUPLER TORSIONAL STIFFNESS	916 (In. Lbs)	1718 (In. Lbs)	1718 (In. Lbs)
ELECTRICAL REQUIREMENTS	115V	115V	115V
LID SAFETY SWITCH	Standard	Standard	Standard
SURE-FLEX DRIVE SHAFT COUPLER	Standard	Standard	Standard
NUMBER OF BASKETS	One	Two	One
LOAD CAPACITY WITH MEDIA	60 Lbs.	120 Lbs.	120 Lbs.
BASKET DIMINSIONS	8" X 12" X 12"	(2) 8" X 12" X 12"	12" X 12" X 17"
TIMER SWITCH	30 Minute	30 Minute	30 Minute
SOLUTION CAPACITY	5 Gal.	10 Gal.	10 Gal.
FLOOR SPACE REQUIRED	20"W X 31"L X 31"H	20"W X 39"L X 31"H	20"W X 39"L X 31"H
ALL STEEL CONSTRUCTION	12 GA CONT. WELD	12 GA. CONT. WELD	12 GA CONT. WELD
SHIPPING WEIGHT	210 Lbs.	350 Lbs.	350 Lbs
STANDARD ACCESSORIES			
STEEL MEDIA	25 Lbs.	50 Lbs.	50 Lbs.