

| MACHINE SPECIFICATIONS                            |  |  |  |  |
|---|--|--|--|--|
| *Specifications subject to change without notice. |  |  |  |  |
| MODEL   | SW2432-OS                                    | SW2432-HT                                    | SW2444-OS                                    | SW2444-HT                                    |
| <b>WORK CAPACITY</b>                              |  |  |  |  |
| HEIGHT  | 32"  | 32"  | 44"  | 44"  |
| ROLLOUT TURNTABLE                                 | 24"  | 24"  | 24"  | 24"  |
| LOAD WEIGHT CAPACITY                              | 500  | 500  | 500  | 500  |
| <b>FLOOR SPACE REQUIRED</b>                       |  |  |  |  |
| HEIGHT  | 66"  | 66"  | 80"  | 80"  |
| WIDTH   | 55"  | 67"  | 55"  | 67"  |
| LENGTH: DOOR OPEN                                 | 73"  | 73"  | 85"  | 85"  |
| DOOR CLOSED                                       | 53"  | 60"  | 53"  | 60"  |
| LOADING HEIGHT                                    | 27"  | 27"  | 27"  | 27"  |
| <b>CLEANING SYSTEM</b>                            |  |  |  |  |
| SOLUTION CAPACITY                                 | 70 gals.                                     | 95 gals.                                     | 70 gals.                                     | 95 gals.                                     |
| PUMP MOTOR  | 5 HP   | 5 HP   | 5 HP   | 5 HP   |
| PUMP OUTPUT                                       | (50 psi @ 80gpm)                             | (50 psi @ 80gpm)                             | (50 psi @ 80gpm)                             | (50 psi @ 80gpm)                             |
| SPRAYNOZZLES                                      | 23   | 23   | 23   | 23   |
| MANIFOLD SIZE                                     | 1.5" WELDED                                  | 1.5" WELDED                                  | 1.5" WELDED                                  | 1.5" WELDED                                  |
| MANIFOLD CONFIGURATION                            | 360  | 360  | 360  | 360  |
| FILTER SCREEN                                     | 695 sq."                                     | 1290 sq."                                    | 695 sq."                                     | 1290 sq."                                    |
| TURNTABLE DRIVE                                   | GEAR DRIVE                                   | GEAR DRIVE                                   | GEAR DRIVE                                   | GEAR DRIVE                                   |
| <b>CABINET CONSTRUCTION</b>                       |  |  |  |  |
| GAUGE STEEL                                       | 12 gauge                                     | 12 gauge                                     | 12 gauge                                     | 12 gauge                                     |
| STEAM VENT  | 6"   | 6"   | 6"   | 6"   |
| GAS VENT  | 4"   | 4"   | 4"   | 4"   |
| DOOR DESIGN                                       | LAY DOWN                                     | LAY DOWN                                     | LAY DOWN                                     | LAY DOWN                                     |
| DOOR SEALS  | NONE   | NONE   | NONE   | NONE   |
| <b>HEAT SOURCE</b>                                |  |  |  |  |
| ELECTRIC ELEMENT                                  | 10 KW  | 10 KW  | 10 KW  | 10 KW  |
| GAS BURNER  | 75,000 btu                                   | 85,000 btu                                   | 75,000 btu                                   | 85,000 btu                                   |
| <b>HOT TANK BASKETS</b>                           |  |  |  |  |
| WIDTH (I.D.)                                      | 9"   | 21"  | 9"   | 21"  |
| LENGTH (I.D.)                                     | 30"  | 34"  | 30"  | 34"  |
| DEPTH (I.D.)                                      | 10"  | 11"  | 11"  | 11"  |
| <b>ELECTRICAL REQ.</b>                            |  |  |  |  |
| PUMP MOTOR 3 PHASE AMP DRAW                       | 208 / 230 / 460 Volts<br>13 12 6.0 Amps      |  | 208 / 230 / 460 Volts<br>13 12 6.0 Amps      |  |
| ELECTRIC HEAT 3 PHASE AMP DRAW                    | (10 KW<br>208/230/460 Volts<br>28-25-13 Amps | (10 KW<br>208/230/460 Volts<br>28-25-13 Amps | (10 KW<br>208/230/460 Volts<br>28-25-13 Amps | (10 KW<br>208/230/460 Volts<br>28-25-13 Amps |
|   |  |  |  |  |
| <b>*ELECTRICAL OPTIONS</b>                        |  |  |  |  |
| 5 HP PUMP MOTOR 1 PHASE                           | 230 Volts, 21 Amps                           |  | 230 Volts, 21 Amps                           |  |
| ELECTRIC HEATER 1 PHASE                           | (10 KW) 230 Volts<br>44 Amps                 | (10 KW) 230 Volts<br>44 Amps                 | (10 KW) 230 Volts<br>44 Amps                 | (10 KW) 230 Volts<br>44 Amps                 |
|   |  |  |  |  |
| Shipping Weight                                   | 1000 lbs                                     | 1300 lbs                                     | 1000 lbs                                     | 1300 lbs                                     |
| <b>STANDARD EQUIPMENT</b>                         |  |  |  |  |
| LOW WATER SWITCH                                  | STANDARD                                     |  | STANDARD                                     |  |
| DUAL 7 DAY TIMERS                                 | STANDARD                                     |  | STANDARD                                     |  |
| DIGITAL TEMP CONTROLLER                           | STANDARD                                     |  | STANDARD                                     |  |
| ADJUSTABLE HEAD RACK/CRANK RACK                   | STANDARD                                     |  | STANDARD                                     |  |
| AUTO AIR INDUCER                                  | STANDARD                                     |  | STANDARD                                     |  |
| SHORT CIRCUIT PROTECTION                          | STANDARD                                     |  | STANDARD                                     |  |
| THERMAL PROTECTION                                | STANDARD                                     |  | STANDARD                                     |  |
| LAY DOWN DOOR/SEALESS                             | STANDARD                                     |  | STANDARD                                     |  |
| V-BOTTOM FLOOR                                    | STANDARD                                     |  | STANDARD                                     |  |
| BUILT IN HOT TANK                                 | STANDARD                                     |  | STANDARD                                     |  |
| 360 DEGREE MANIFOLD                               | STANDARD                                     |  | STANDARD                                     |  |
| WARRANTY  | ONE YEAR                                     |  | ONE YEAR                                     |  |
| INSULATION  | OPTIONAL                                     |  | OPTIONAL                                     |  |